

VORONEZH SYNTHETIZKACHUK JSC

SAFETY DATA SHEET

According to 1907/2006/EC, article 31 (REACH)

STYRENE-BUTADIENE RUBBER (SSBR)

Solution type

GRADES

SSBR -2525; SSBR -2545; SSBR -2560

Version: 2.1
Created: 11/05/2012
Regulation: EC No 1272/2008

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

1.1 Product identifier

Name of Substance:	Styrene Butadiene Rubber (Solution type)
Name of IUPAC	benzene, ethenyl-, polymer with buta-1,3-diene
Synonyms	Poly(styrene- <i>co</i> -butadiene)
Product Grades	SSBR -2525; SSBR -2545; SSBR -2560
Registration # for 1,3-butadiene (CAS #106-99-0; EC #203-450-8) <i>Index No(CLP): 601-013-00-X</i>	01-2119471988-16-0034 01-2119471988-16-0033
Registration for styrene (CAS #100-42-5; EC #202-851-5) <i>Index No(CLP): 601-026-00-0</i>	01-2119457861-32-0016

DISCLAIMER

This product is a polymer and is not classified as dangerous under criteria of Directives No 67/458/EEC, No 1999/45/EC and Regulation (EC) No 1272/2008 (Regulation CLP). This polymer does not contain substances classified as dangerous under Article 59.2 Regulation (EC) No 1272/2008, namely:

- in an individual concentration of ≥ 1 % by weight for non-gaseous mixtures posing human health or environmental; or*
- in an individual concentration of ≥ 0.1 % by weight for non-gaseous mixtures that is carcinogenic category 1, 2 or toxic to reproduction category 1A, 1B and 2, skin sensitiser category 1, respiratory sensitiser category 1, or has effects on or via lactation or is persistent, bioaccumulative and toxic (PBT) in accordance with the criteria set out in Annex XIII REACH or very persistent and very bioaccumulative (vPvB) in accordance with the criteria set out in Annex XIII REACH; or*
- a substance for which there are Community workplace exposure limits.*

In accordance with mentioned above, this product does not require and official e-SDS as per Regulations (EC) No 1907/2006 (articles 31.1; 31.2) and Commission Regulation (EU) No 453/2010.

This e-SDS is developed in good faith to provide a customer with sufficient information allowing to take necessary measures to comply with relevant HSE requirements.

1.2 Relevant identified uses of the substance

Most common technical function of Styrene Butadiene Rubber (Solution type): tyre production, technical rubber parts (profiles, hoses, shoe soles, belt production, technical rubber goods), rubber compound.

1.3 Details of the supplier of the safety data sheet

Only representative:

Company name: Gazprom Marketing and Trading France
Address: 68 avenue des Champs-Élysées, 75008, Paris, France
Contact Telephone: +33 1 42 99 73 50
Fax: +33 1 42 99 73 99
Email Address: Yury.severinchik@gazprom-mt.com

Suppliers:

Company name: Voronezhsynthetkauchuk JSC
Address: 2, Leninsky avenue, Voronezh, Russian Federation, 394014
Phone: +7 473 220-65-26
Fax: +7 473 220-69-40, 20-68-19
Email Address: officer@vrnsk.vrn.ru
Emergency phone: +7 473 220-67-40

Emergency phone in the country of delivery: 112 (Please note that emergency numbers may vary depending upon the country of delivery though 112 remains valid as universal number)

SECTION 2. HAZARDS IDENTIFICATION

Classification:

ANNEX I OF DIRECTIVE 67/548/EEC:

Physical/Chemical Hazards:
None.

Health Hazards:
None.

Environmental hazards:
None.

EU CLP 2008:

Physical/Chemical Hazards:
None.

Health Hazards:
None.

Environmental hazards:
None.



Specific hazard:

No significant health hazard in normal industrial use conditions.
Contact with melted/ heated product may cause thermal burns.
Processing vapours, which can irritate eyes and respiratory tract, may form when product is heated at high temperatures.
Combustible solid.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

This product is a synthetic rubber, consisting of at least 98.0% co-polymer from styrene and butadiene (23-27% bound styrene), 0.2-0.4% antioxidant (CAS#82209-88-9). May contain traces of styrene (< 0.05%).

Name	EC #	CAS #	Content,%	Classification EC#67/548/EEC and EC#1272/2008 (CLP)
Poly(styrene-co-butadiene)	none	9003-55-8	≥ 98.0	none

The product does not contain impurities or additives that could affect product's labelling and classification according to Regulation (EC) No 67/548/EEC and Regulation (EC) No 1272/2008 (CLP) in the concentration ranges specified.

SECTION 4. FIRST-AID MEASURES

General information:

Spontaneous penetration of styrene-butadiene rubber into human organism is impossible.
Styrene-butadiene rubber at normal conditions is stable and non-volatile.
Under high temperatures and during rubber processing release of monomer vapors are possible which in poor ventilated areas may cause irritation of eyes mucous and upper respiratory ways.
Contact with eyes may cause mechanical damage, irritation of eyes mucous, delacrimation.
No significant health hazard in normal industrial use conditions.
Contact with melted/ heated product may cause thermal burns.

Inhalation:

In emergency and in case of poisoning by rubber combustion products or if decomposition or thermal destruction products are inhaled:
Move an exposed person to fresh air at once. Keep warm and at rest. If there is respiratory distress give oxygen. If respiration stops or shows signs of failing, apply artificial respiration. Get medical attention.

Ingestion:

In case of accidental swallowing:
Wash out mouth with water and give plenty of water to drink, provided person is conscious. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If vomiting occurs naturally, have the exposed person lean forward. Get medical attention.



Skin contact:

There are no risks in normal industrial use conditions. In case of contact with hot product remove contaminated clothing and wash skin with plenty of running water. Get medical attention.

Eye contact:

Rinse the eye immediately with plenty of water (low pressure) for at least 15 minutes.
Remove contact lenses. Get medical attention.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing media:

Use foam, dry chemical, carbon dioxide, sand or water spray.

Special fire fighting procedures:

Keep away from sources of ignition – no smoking.
Extinguish fire keeping safe distance. Not yet ignited rubber briquettes to be kept cool by means of water spraying.

Unusual fire & explosion hazards:

None.

Specific hazards:

Combustion generates irritating and toxic fumes.
Burning causes emissions of carbon oxide.

Protective measures in fire:

Wear canvas protective suit, gloves, helmets, face shields, rubber or kersey boots, gas mask.
In proximity to fire wear full protective clothing and MSHA/NIOSH-approved self-contained breathing apparatus with full face piece operated in the pressure demand or other positive pressure mode.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions:

See section 8.

Individual safety measures:

Remove sources of ignition.

Provide workplace ventilation, process equipment and communication sealing, air monitoring of the workplace, avoid contact with skin and eyes.

Environmental precautions:

Do not allow penetration of the product into water reservoirs, surface and ground water, sewer ducts and soil. Preventing disposal into water reservoirs of contaminated water without treatment.
Monitor content of hazardous substances in the air.
Provide sealing of process equipment.

Spill clean-up methods:

Absorb spill with inert material (e.g. vermiculite, sand or earth), then place in suitable container.

SECTION 7. HANDLING AND STORAGE

Handling:

Handle in accordance with good industrial hygiene and safety practice.
Provide input-extract and local ventilation of work zones.
Provide thorough sealing and grounding of process equipment.
Regularly control work zone air.

Usage precaution:

Use in accordance with safety measures, rules of personal hygiene and industrial sanitation in the production at the facility.
Avoid contact with eyes and skin. Do not ingest or inhale combustion or decomposition products.

Storage precautions:

Store in a dry, well-ventilated area, at temperature not exceeding 30°C.
Keep away from direct sunlight, atmospheric precipitation and incompatible substances in a closed container. Prevent from freezing.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure limits:

None listed.

Personal protective equipment:

Respiratory tract:

Not required (if is used workplace conditions).

In emergency or in case of increase of hazardous substances concentration at the workplace wear positive pressure MSHA/NIOSH-approved self-contained breathing apparatus.

Hand protection:

Wear approved protective gloves.

Eye protection:

Wear approved safety goggles.

Skin protection:

Wear protective clothing and footwear, in contact with the hot product wear thermally resistant gloves.

Hygiene measures:

Personal hygiene and industrial sanitation in the production at the facility (wash hands at the end of each work shift and before eating, drinking, smoking or using the toilet).

Technical safety measures:

Forced-air and exhaust ventilation in work zones.

Compulsory monitoring of air conditions in work areas.
Sealing and grounding of equipment and communications.
Usage of intrinsically safe equipment.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state at 20°C and 1013 hPa	elastic solid (firm homogeneous spongy mass)
Appearance	rubber is produced in the form of briquettes
Odour	peculiar
Colour	creamy to light brown
pH value	not applicable, insoluble
Melting point	> 200 °C
Ignition temperature	> 315 °C
Auto-ignition temperature	> 400 °C
Relative density	1.0 g/cm ³
Solubility	insoluble in water. soluble in aromatic and aliphatic solvents (benzene, toluene, heptane, hexane, benzene)
Flammability	does not ignite spontaneously, burn only upon entering into a source of fire
Explosive properties	non explosive
Average molecular weight	200000-260000
Granulometry	not applicable, substance is not marketed or used in granular form

SECTION 10. STABILITY AND REACTIVITY

Stability:

Stable under normal temperatures and pressures.

Materials to avoid:

Strong oxidising agents, acids and alkalis.

Reactivity:

Undergoes oxidation, oxidative destruction.

Conditions to avoid:

Avoid high temperatures. Avoid naked flame. Avoid long term exposure to direct sun beams. Avoid contact with incompatible substances.

Hazardous decomposition products:

Carbon monoxide, carbon dioxide.

SECTION 11. TOXICOLOGICAL INFORMATION

General information:

No significant health hazard in normal industrial use conditions.

Acute toxicity:

LD₅₀ (oral, rats): > 5000 mg/kg

Inhalation toxicity: very low toxicity.

The substance is a non-volatile elastic solid and is produced in the form of briquettes. There is therefore no potential for inhalation exposure.

Irritation/Corrosivity:

Skin: none

Eye: none

Respiratory tract: none

Sensitisation:

Skin: none

Eye: none

Respiratory tract: none

Cumulative: low

Carcinogenicity: no carcinogenic effects

Mutagenicity: negative

Toxicity for reproduction: not investigated

Repeated dose toxicity: not investigated

Reference: Russian Register of Potentially Hazardous Chemical and Biological Substances /FBEPH.

SECTION 12. ECOLOGICAL INFORMATION

General information:

At normal conditions rubber is a very stable product

Does not form toxic compounds with other substances in air and water

The product is poorly biodegradable but does not pose a hazard to the environment

Pollution of water ponds and soil with polymer flakes may occur only if production, handling and transportation rules are not followed, in case of effluent discharge without treatment, as a result of emergencies and accidents

Aquatic toxicity: not investigated

Abiotic degradation: $t_{1/2}$: > 30 d extremely stable

Chemical degradation: not investigated

Bioaccumulative potential: not investigated

Mobility in soil: not investigated

Reference: Russian Register of Potentially Hazardous Chemical and Biological Substances /FBEPH

Water hazard classification

According to the German VwVwS: WGK- 0 (not classified)

SECTION 13. DISPOSAL CONSIDERATIONS

General information:

Place into a suitable closed container for disposal.

Disposal methods:

Dispose in accordance with local and national regulations.

Waste water containing rubber should be treated.

Packaging waste (paper bags) shall be collected and send for recycling. Plastic waste shall be removed to disposal.

SECTION 14. TRANSPORT INFORMATION

General:

The product is not covered by international regulations on the transport of dangerous goods.

UN: none.

SECTION 15. REGULATORY INFORMATION

Chemical Safety Report has been performed for monomers: 1,3-butadiene (CAS #106-99-0; EC #203-450-8), styrene (CAS #100-42-5; EC #202-851-5).

SECTION 16. OTHER INFORMATION

16.1 Indication of changes:

VERSION	Date of change	Section	Description of changes
Version: 1.0	10/02/2010		First edition created according to recommendations of Regulations (EC) #1907/2006 (Article 31.1).
Version: 2.0	07/02/2011	1.1, 2	Sections 1.1, 2 were updated.
Version: 2.1	11/05/2012	1; 3; 4; 5; 6; 7; 8; 9; 10; 11; 12; 15; 16	1 Product name STYRENE-BUTADIENE RUBBER (DSSK) was changed into STYRENE-BUTADIENE RUBBER (SSBR) and grade's names (DSSK - 2525; DSSK - 2545; DSSK - 2560) were changed into (SSBR-2525; SSBR-2545; SSBR-2560) accordingly. 2. Section 1.1 was updated. 3. DISCLAIMER was added on the first page. 4. Section 1.3 was updated (E-mail address, Emergency phone for suppliers). 5. Sections 4: General information subsection was added. Inhalation Subsections were updated was updated. 6. Section 5. Extinguishing media, Special fire fighting procedures were updated. 7. Section 6: Individual safety measures, Environmental precautions were updated. 8. Section 7. Storage precautions, Handling Subsections were updated.

			9. Section 8: Personal protective equipment, Hygiene measures, Technical safety measures Subsections were updated. 10. Sections 3, 9, 10; 11; 12; 15; 16 were fully updated.
--	--	--	---

16.2 Relevant R-phrases, Hazard- and EU Hazard-statements

Labelling: none.

R-phrases: none.

Safety Advice (S-phrases):

- S 16 Keep away from sources of ignition - no smoking
S 41 In case of fire and/or explosion do not breathe fumes
S 47 Keep at temperature not exceeding 30°C

16.3 Abbreviations and acronyms

- LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)
STOT Specific Target Organ Toxicity
PBT Persistent, bioaccumulative, toxic chemical
vPvB Very Persistent, Very Bioaccumulative
UN United Nations
WGK Wassergefährdungsklasse (*German: Water Hazard Class*)

16.4 Key literature references and sources

EU DIRECTIVES

REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

Regulation (EC) No 1272/2008 REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Regulations. Commission regulation (EU) no 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH).

DIRECTIVE 1999/45/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 31 May 1999 concerning the approximation of the laws, regulations and administrative provisions of the Member States relating to the classification, packaging and labelling of dangerous preparations
Directive 67/548/EEC on the approximation of the laws, regulations and administrative provisions relating to the classification, packaging and labeling of dangerous substances.



VERSION: 2.1
DATE CREATED: 11/05/2012

COMMISSION DECISION of 16 January 2001 amending Decision 2000/532/EC as regards the list of wastes (notified under document number (2001/118/EC).

NATIONAL REGULATIONS (GERMANY)
Major Accident Hazard Legislation 82/501/EWG.

Russian Register of Potentially Hazardous Chemical and Biological Substances (FBEPH). BENZENE, ETHENYL-, POLYMER WITH BUTA-1,3-DIENE. Dossier of potentially hazardous chemical and biological substance #77.99.27.15.Y.2564.3.05, Ministry of Health of the Russian Federation.

DISCLAIMER

This information is based on our current level of knowledge. This information may be subject to revision as new knowledge and experience becomes available, and SIBUR makes no warranties and assumes no liability in connection with any use of this information. Since SIBUR cannot be aware of all aspects of your business and the impact the REACH Regulation has for your company, SIBUR strongly encourages you to get familiar with the REACH Regulation in order to comply with its requirements and timelines.