

## SIBUR-KSTOVO LLC

### SAFETY DATA SHEET

According to Regulations (EC) 1907/2006 (REACH), (EC) 1272/2008 (CLP) & (EU) 2015/830

## PROPENE

Version: 3.0  
Date created: 25/01/2019

#### SECTION 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

##### 1.1. Product identifier

Product form: Substance  
Substance name: Propene  
Chemical name: Propene, Prop-1-ene  
EC index No.: 601-011-00-9  
EC No.: 204-062-1  
CAS-No.: 115-07-1  
REACH registration No: 01-2119447103-50-0052  
Formula: C<sub>3</sub>H<sub>6</sub>  
Synonyms: Propylene, Methylethylene, Methylethene  
Trade names: Propylene, Propene

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

###### 1.2.1. Relevant identified uses

Use of the substance/mixture: Formulation & (re)packing of substances and mixtures  
Distribution of substance  
Use as a fuel  
Use as an intermediate  
Polymer Production  
Use as a propellant  
*For the detailed identified uses of the product see Annex.*

Most common technical function of substance: Aerosol propellants  
Intermediates  
Fuels and fuel additives

###### 1.2.2. Uses advised against

Restrictions on use: Uses other than those given in section 1.2.1 are not recommended unless an assessment is completed, prior to commencement of that use, which demonstrates that the use will be controlled

##### 1.3. Details of the supplier of the safety data sheet

###### Only representative

Company name: Gazprom Marketing and Trading France  
Address: 68 avenue des Champs-Élysées, 75008, Paris, France  
Contact Telephone: +33 1 42 99 73 50  
Fax: +33 1 42 99 73 99  
Email Address: didier.lebout@gazprom-mt.com

### Manufacturer

Company name: SIBUR-KSTOVO LLC  
Address: 607650 Russian Federation, Nizhny Novgorod oblast, Kstovsky district, city of Kstovo, urban Industrial district, residential district, South, a quarter of SIBUR-South passage, 4, building №2  
Contact phone: +7 83145 9 49 03  
Fax: +7 83145 9 49 10  
Email Address: info@sk.sibur.ru  
servicedbp@sibur.ru  
Emergency Telephone: +7 83145 9 49 10 (round the clock)  
Importer: List of importers is available with the Only Representative

### 1.4. Emergency telephone number

Emergency phone in the country of delivery **112** (Please note that emergency numbers may vary depending upon the country of delivery though 112 remains valid as universal number)

## SECTION 2. HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Gas 1 H220

Liquefied gas H280

Full text of hazard classes and H-statements : see section 16

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP):



GHS02

GHS04

Signal word (CLP):

Danger

Hazard statements (CLP):

H220: Extremely flammable gas.

(CLP):

H280: Contains gas under pressure; may explode if heated.

Precautionary statements (CLP):

P210: Keep away from heat/sparks/open flames/... /hot surfaces.... No smoking.

P377: Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

P381: Eliminate all ignition sources if safe to do so.

P403: Store in a well-ventilated place.

EUH-statements:

Not applicable.

### 2.3. Other hazards

Other hazards not contributing to the classification:

Contact with the liquid may result in frostbite.

Assessment PBT / vPvB:

According to Annex XIII of Regulation (EC) No.1907/2006 (REACH):  
- not fulfilling PBT (persistent/bioaccumulative/toxic) criteria;  
- not fulfilling vPvB (very persistent/very bioaccumulative) criteria.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1. Substances

Name	Product identifier	%	Classification [CLP]
Propene	(CAS-No.) 115-07-1 (EC No.) 204-062-1 (EC index No.) 601-011-00-9 (REACH-no) 01-2119447103-50-0052	99.0 – 99.9	H220 H280

The product does not contain impurities or additives that could affect product's labelling and classification according to Regulation (EC) No 1272/2008 (CLP).

### 3.2. Mixtures

Not applicable

## SECTION 4. FIRST-AID MEASURES

### 4.1. Description of first aid measures

#### Product-specific hazards and other issues

Extremely flammable liquefied gas. An asphyxiant at high concentrations – oxygen depletion can be fatal. Contact with the liquid may result in frostbite.

#### First-aid measures general

Before attempting to rescue casualties, isolate area from all potential sources of ignition including disconnecting electrical supply. Ensure adequate ventilation and check that a safe, breathable atmosphere is present before entry into confined spaces. Take care to self-protect by avoiding becoming contaminated – use approved positive pressure air supplied breathing apparatus with a full facepiece. Move contaminated patient(s) out of the dangerous area. Seek medical assistance - show the material safety data sheet or label if possible.

#### First-aid measures after inhalation

Move to fresh air. Do not leave the victim unattended. Keep patient warm and at rest. Exposure to high concentrations may cause asphyxiation and the victim may be unaware. If unconscious place in recovery position. Seek immediate medical attention. If breathing is difficult, give oxygen if possible, or assisted ventilation. In the event of cardiac arrest, (no pulse), apply cardiopulmonary resuscitation.

#### First-aid measures after skin contact

Do not remove clothing that adheres due to freezing. Immediately flush affected area with plenty of water – continue for at least 15 minutes. If there are signs of frostbite, (blanching or redness of skin or burning or tingling sensation), do not rub, massage or compress the affected area. Send the casualty immediately to hospital.

#### First-aid measures after eye contact

Remove any contact lenses. Flush eyes with water thoroughly and continuously for at least 15 minutes. Keep eye wide open while rinsing. If there are signs of frostbite, pain, swelling, lacrimation or photophobia persists, the patient should be seen in a specialist health care facility.

#### First-aid measures after ingestion

Is not considered a likely route of exposure – frostbite to the lips and mouth may occur if in contact with the liquid.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation: Headache weakness, dizziness, drowsiness. Exposure to high concentrations may cause asphyxiation, unconsciousness.

Symptoms/effects after skin contact: Frostbite, redness, edema, pain.

Symptoms/effects after eye contact: Frostbite, pain, swelling, lacrimation or photophobia.

Symptoms/effects after ingestion: Is not considered a likely route of exposure – frostbite to the lips and mouth may occur if in contact with the liquid.

### 4.3. Indication of any immediate medical attention and special treatment needed

#### Advice to physician

A simple asphyxiant gas at normal temperatures and pressures – there is no specific antidote. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled In the event of contact with product in liquid form treat for frostbite.

## SECTION 5. FIRE-FIGHTING MEASURES

### 5.1. Extinguishing media

Suitable extinguishing media: LARGE FIRE: Use water spray, water fog or foam.  
SMALL FIRE: Dry powder or carbon dioxide (CO<sub>2</sub>) extinguisher, dry sand or fire fighting foam

Unsuitable extinguishing media: Do NOT use water jet.  
Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard: Vapour is denser than air – flashback may be possible over considerable distances.

Explosion hazard: Cylinders or other containment vessels may explode under fire conditions - use water spray to cool unopened containers. Do not allow run-off from fire fighting to enter drains or water courses – may cause explosion hazard in drains and may reignite.

Hazardous decomposition products in case of fire: Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

### 5.3. Advice for firefighters

Firefighting instructions: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. First move people out of line-of-sight of the scene and away from windows.  
If gas has ignited, do not attempt to extinguish but stop gas flow and allow to burn out. Use water spray to cool heat-exposed containers, and to protect surrounding areas and personnel effecting shut-off. Every precaution must be taken to keep containers cool to avoid the possibility of a boiling liquid expanding vapour explosion (BLEVE). Pressurised containers are liable to explode violently when subjected to high temperatures.

Protection during firefighting: Fire-fighters should wear an approved positive pressure self-contained breathing apparatus (SCBA) with a full face-piece in addition to standard fire-fighting gear.

Further information: Not available.

## SECTION 6. ACCIDENTAL RELEASE MEASURE

### 6.1. Personal precautions, protective equipment and emergency procedures

Spillages of material generate large volumes of extremely flammable gas which is heavier than air

and will accumulate in low areas or confined spaces. Wear personal protective equipment, including self contained breathing apparatus, unless the atmosphere is proved to be safe.

#### 6.1.1. For non-emergency personnel

Emergency procedures No action shall be taken involving any personal risk or without suitable training. Accidental releases pose a serious fire or explosion hazard. Avoid direct contact with released material and breathing vapours. Stay upwind. Immediately contact emergency personnel.

#### 6.1.2. For emergency responders

Emergency procedures Stop leak if safe to do so. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Enter area only if strictly necessary. Eliminate all ignition sources. Avoid direct contact with released material and breathing vapours. Use suitable protective equipment. Ensure good ventilation. Follow all fire-fighting procedures. A gas detector or instrument to detect explosive atmospheres (explosimeter) can be used to check for combustible gas or vapour in an atmosphere, but it needs care and training to be used safely. Do not enter a vapour cloud except for rescue; self-contained breathing apparatus must be worn. Liquid leaks generate large volumes of extremely flammable gas. If required, notify relevant authorities according to applicable regulations.

#### 6.2. Environmental precautions

Land spillage: Prevent further leakage or spillage if safe to do so. Prevent spillage from entering drains or any place where accumulation may occur. Ensure adequate ventilation, especially in confined areas.

Spillages in water or at sea: Prevent further leakage or spillage if safe to do so. Spillages of liquid product in the water will likely result in a quick and complete vaporization of the product. Isolate the area and prevent fire/explosion hazard for ships and other structures, taking into account wind direction and speed, until the material is completely dispersed. If the spillage contaminates rivers, lakes or drains inform respective authorities.

#### 6.3. Methods and material for containment and cleaning up

Contain spillage – ventilate area and allow to evaporate.

#### 6.4. Reference to other sections

SECTION 8: Exposure controls/personal protection. SECTION 13: Disposal considerations.

### SECTION 7. HANDLING AND STORAGE

#### 7.1. Precautions for safe handling

Precautions for safe handling Smoking, eating and drinking should be prohibited. Use only in well ventilated areas. Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Avoid all sources of ignition, oxidising agents, chlorine and hydrogen chloride or hydrogen fluoride. Take precautionary measures against static discharges, use proper bonding and/or grounding procedures. Avoid contact with heat and ignition sources and oxidizing agents. Use only in a closed system. Use piping and equipment designed to withstand the pressures to be

encountered.

Use a check valve or other protective device to prevent reverse flow. Cleaning, inspection and maintenance of the internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Handle empty containers with care; vapour residue may be flammable. Do not pressurise, cut, weld, braze, solder, drill, or grind on containers. Dispose of rinse water in accordance with local and national regulations.

The vapour is heavier than air, beware of accumulation in pits and confined spaces.

Ensure that all relevant regulations regarding explosive atmospheres, and handling and storage facilities of flammable products are followed.

Hygiene measures

Wash thoroughly after handling. Wash your hands at the end of each work shift, before and after eating, drinking, or using the toilet.

## 7.2. Conditions for safe storage, including any incompatibilities

Incompatible materials

Oxidizing agents, strong acids, water, nitrogen oxides (NO, NO<sub>2</sub> etc.), explosive materials, flammable substances, pyrophoric substances, organic peroxides and self reactive substances, combustible substances. See also Section 10 of this SDS.

Storage area

Keep away from heat, sparks, and flame. Keep away from sources of ignition. Store in a tightly closed container.

Store and use only in equipment/containers designed for use with this product. Containers must be properly labelled. Do not remove warning labels from containers.

Cylinders should be secured vertical - and only transported in a secure position in a well ventilated vehicle or hand truck.

Cylinders which have been are opened must be carefully resealed and kept upright.

For maintenance work or conservation, emptied tanks should be purged, and blanketed with inert gas (i.e. nitrogen).

Packaging materials

Keep/Store only in original container.

## 7.3. Specific end use(s)

Not applicable.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

#### 8.1.1. Occupational Exposure Limits

<i>Propene (CAS#115-07-1)</i>					
	LTEL TWA ppm	LTEL TWA mg/m <sup>3</sup>	STEL ppm	STEL mg/m <sup>3</sup>	Note
<b>European Union</b>					
Denmark	100	172	200	344	
Finland	500				
Poland		2000		8600	
Latvia		100			
Spain	500	-	-	-	

Sweden	500	900			
Switzerland	10000	17500			

### 8.1.2. DNEL/ PNEC values

#### *Propene (CAS#115-07-1)*

##### **DNEL/DMEL (Workers)**

Acute - systemic effects, dermal	No hazard identified
Acute - systemic effects, inhalation	No hazard identified
Acute - local effects, dermal	No hazard identified
Acute - local effects, inhalation	No hazard identified
Long-term - systemic effects, dermal	No hazard identified
Long-term - systemic effects, inhalation	No hazard identified
Long-term - local effects, dermal	No hazard identified
Long-term - local effects, inhalation	No hazard identified

##### **DNEL/DMEL (General population)**

Acute - systemic effects, dermal	No hazard identified
Acute - systemic effects, inhalation	No hazard identified
Acute - systemic effects, oral	No hazard identified
Acute - local effects, dermal	No hazard identified
Acute - local effects, inhalation	No hazard identified
Long-term - systemic effects, dermal	No hazard identified
Long-term - systemic effects, inhalation	No hazard identified
Long-term - systemic effects, oral	No hazard identified
Long-term - local effects, dermal	No hazard identified
Long-term - local effects, inhalation	No hazard identified

##### **PNEC (water)**

PNEC aqua (freshwater)	No hazard identified
PNEC aqua (marine water)	No hazard identified
PNEC aqua (intermittent, freshwater)	No hazard identified

##### **PNEC (Sediment)**

PNEC sediment (freshwater)	No hazard identified
PNEC sediment (marine water)	No hazard identified

##### **PNEC (Soil)**

PNEC soil	No hazard identified
-----------	----------------------

##### **PNEC (Oral)**

PNEC oral (secondary poisoning)	No potential for bioaccumulation
---------------------------------	----------------------------------

##### **PNEC (STP)**

PNEC sewage treatment plant	No hazard identified
-----------------------------	----------------------

### 8.2. Exposure controls

#### **Appropriate engineering controls:**

Closed system. Provide adequate ventilation. Use only in area provided with appropriate exhaust ventilation. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Take precautionary measures against static discharge. Provide adequate precautions, such as electrical grounding and bonding, or inert atmospheres. Use only explosionproof equipment. Organisational measures to prevent /limit releases, dispersion and exposure. See also Section 7 of this SDS.

Recommended monitoring procedures: If this product contains ingredients with exposure limits,

personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to European Standard EN 689 for methods for the assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances.

**Hand protection:**

The selection of specific gloves for a specific application and time of use in a working area, should also take into account other factors on the working space, such as (but not limited to): other chemicals that are possibly used, physical requirements (protection against cutting/drilling, skill, thermal protection), and the instructions/specification of the supplier of gloves. Protective gloves against cold (EN 511).

Breakthrough time: 4-8 hours

Suitable materials: neoprene , nitrile rubber

**Eye protection:**

Approved eye protection to safeguard against potential eye contact, irritation, or injury is recommended. Depending on conditions of use, a face shield may be necessary. Wear approved safety goggles (BS EN 166, 167 and 168)

**Skin and body protection:**

Use body protection appropriate for task. Transfer of large quantities under pressure may require protective equipment appropriate to protect employees from splashes of liquefied product, as well as fire retardant items. If a hazard of injury to the feet exists due to falling objects, rolling objects, where objects may pierce the soles of the feet or where employee's feet may be exposed to electrical hazards, use foot protection

**Respiratory protection:**

In emergency or in case of increase of hazardous substances concentration at the workplace wear positive pressure MSHA/NIOSH-approved self-contained breathing apparatus (BS EN 14387:2004).

**Environmental exposure controls:**

Do not allow entrance in sewage water, drainage systems, stretches of water, soil. Avoid penetration into drainage system or in rooms situated at a lower level because of danger of explosion. Issue an immediate alarm report to the company environmental protection department if the product unintentionally leaves the production area.

**Other information:**

Hygiene measures: Do not inhale vapours / aerosols. Avoid contact with skin and eyes. Change clothing that has been in contact with or taken up any of the gas and air the clothing far from any sources of ignition. Smoking, eating and drinking should be prohibited in the application area. Observe the rules usually applicable when handling chemicals.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

**9.1. Information on basic physical and chemical properties**

Physical state at 20 °C and 101.3 kPa	Gaseous
Melting / freezing point	- 185 °C
Boiling point	- 48 °C
Relative density	Not applicable
Vapour pressure	Not applicable
Surface tension	Not applicable
Water solubility	200 mg/l at 25 °C



Partition coefficient n-octanol/water (log value)	Log Kow (Pow): 1.77 at 20 °C
Flash point	Not applicable
Flammability	Extremely flammable. The lower and upper explosive limits of propene are 2-11% by volume. This endpoint will result in a classification of Category 1 for flammable gases with a hazard statement of extremely flammable gas.
Explosive properties	Not applicable
Self-ignition temperature	455 °C at 1013 hPa
Oxidising properties	Not applicable
Viscosity	Not applicable
Granulometry	Not applicable
Stability in organic solvents and identity of relevant degradation products	Not applicable
Dissociation constant	Not applicable

## 9.2. Other information

Not available.

## SECTION 10. STABILITY AND REACTIVITY

### 10.1. Reactivity

Liquefied gas. Extremely flammable. Stable at room temperature in closed containers under normal storage and handling conditions.

The substance can polymerise with fire or explosion hazard.

### 10.2. Chemical stability

Stable under normal storage and handling conditions.

### 10.3. Possibility of hazardous reactions

Vapours may form explosive mixture with air. Reacts violently with strong oxidizing agents, Acids.

### 10.4. Conditions to avoid

Keep away from heat and sources of ignition.

### 10.5. Incompatible materials

Strong oxidizing agents, nitrogen oxides. Reacts easily with many materials, such as alkyl halides, halogens, concentrated sulphuric acid, hypochlorous acid, aluminium chloride, carbon monoxide and hydrogen. See also Section 7.2 of this SDS

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. In case of fire or thermal decomposition production of, for example, Carbon monoxide, carbon dioxide (CO<sub>2</sub>).

## SECTION 11. TOXICOLOGICAL INFORMATION

### 11.1. Information on toxicological effects

#### Acute toxicity

In both human and animal studies propene is of low acute toxicity by the inhalation route with LC50 values exceeding the concentrations that would warrant classification under CLP.

Since propene is a gas at room temperature and pressure oral and

dermal toxicity is not considered relevant in this context.

<i>Propene (CAS#115-07-1)</i>	
LD50, oral, rats	Not applicable. The substance is a gas at room temperature
NOAEC, inhalation, rats	10000 ppm (17,200 mg/m <sup>3</sup> ) (14 day repeated exposure study) (weight of evidence)
LD50, dermal, rats	Not applicable. The substance is a gas at room temperature
<b>Skin corrosion/irritation</b>	Not relevant - gas at room temperature
Additional information	Direct skin contact with liquid forms of propene may cause burns and frostbite due to the extreme cold of the liquid.
<b>Serious eye damage/irritation</b>	Not relevant - gas at room temperature
Additional information	Direct mucous membrane contact with liquid forms of propene may cause burns and frostbite due to the extreme cold of the liquid.
<b>Respiratory or skin sensitisation</b>	Not sensitizing.
Additional information	Not relevant - gas at room temperature
<b>Germ cell mutagenicity</b>	Genetic toxicity: no adverse effect observed (negative). CLP classification (Regulation (EC) No 1272/2008): no classification required
Additional information	In vitro genotoxicity studies negative with metabolic activation (with the exception of a weakly mutagenic response in TA1535 only); negative without metabolic activation (S. typhimurium TA 1535, TA 1537, TA 98 and TA 100, E. Coli) (equivalent or similar to OECD Guideline 471) In vivo genotoxicity studies negative (inhalation, rat, male) (OECD Guideline 474)
<b>Carcinogenicity</b>	CLP classification (Regulation (EC) No 1272/2008): no classification required.
<i>Propene (CAS#115-07-1)</i>	
NOAEC (carcinogenicity), inhalation, mouse	10000 ppm (equivalent to 17200 mg/m <sup>3</sup> /day) (OECD Guideline 453)
<b>Toxicity for reproduction</b>	CLP classification (Regulation (EC) No 1272/2008): no classification required.
<i>Propene (CAS#115-07-1)</i>	
NOAEC (effects on fertility), inhalation, rat	300 ppm (equivalent to 710 mg/m <sup>3</sup> ) (OECD Guideline 416) (Read-across, test material: propylene oxide)
NOAEC (developmental toxicity), inhalation, rat	10000 ppm (OECD Guideline 414)
<b>STOT-single exposure</b>	CLP classification (Regulation (EC) No 1272/2008): no classification required. No data available.
<b>Repeated dose toxicity</b>	CLP classification (Regulation (EC) No 1272/2008): no classification required.
<i>Propene (CAS#115-07-1)</i>	
NOAEC (systemic), subchronic, inhalation, rat	10000 ppm (equivalent to 17200 mg/m <sup>3</sup> ) (OECD Guideline 413)

**Aspiration hazard** CLP classification (Regulation (EC) No 1272/2008): no classification required. No data available.

## SECTION 12. ECOLOGICAL INFORMATION

### 12.1. Toxicity

*Propene (CAS#115-07-1)*

#### Fish (Short-term toxicity)

LC50 (96h)	51.7 mg/L (QSAR calculation)
------------	------------------------------

#### Fish (Long-term toxicity)

ChV (30 d)	5.3 mg/L (QSAR calculation)
------------	-----------------------------

#### Aquatic invertebrates (Short-term toxicity)

LC50 (48 h)	28.2 mg/L ( <i>Daphnia sp</i> ) (QSAR calculation)
-------------	--

#### Aquatic invertebrates (Long-term toxicity)

ChV (16d)	3.1 mg/L ( <i>Daphnia sp</i> ) (QSAR calculation)
-----------	---

#### Algae and aquatic plants

EC50/LC50 (96 h)	12.1 mg/L ( <i>green algae</i> ) (QSAR calculation)
------------------	---

ChV (96h)	4.5 mg/L ( <i>green algae</i> ) (QSAR calculation)
-----------	--

#### Toxicity to aquatic micro-organisms

EC10 (18 h)	Not available
-------------	---------------

#### Toxicity to soil macro-organisms

LC50 (14 d)	77.3 ppm ( <i>earthworm (annelids)</i> )(QSAR calculation)
-------------	--

### 12.2. Persistence and degradability

Abiotic degradation:	<u>Phototransformation/ photolysis in air</u> Half-life (DT50):14.6 h (rate constant of 2.63E-11 cm <sup>3</sup> molecule <sup>-1</sup> sec <sup>-1</sup> . Half-life is calculated based on this rate constant and a hydroxyl radical)
----------------------	---

Biodegradation	Readily biodegradable, 50% after 2,36 d (QSAR calculation)
----------------	---

Persistence and degradability	QSAR estimates of biodegradation rate, estimated evaporation rates from the aquatic environment and degradation rates in the atmosphere provide sufficient weight of evidence to conclude that propene can be considered readily biodegradable for the purposes of this risk assessment and does not meet the screening criteria for P/vP.
-------------------------------	--

### 12.3. Bioaccumulative potential

Aquatic bioaccumulation:	Not expected to bioaccumulate due to the low log Kow < 3. Propene has a log Kow of 1.77.
--------------------------	--

Secondary poisoning:	An assessment of secondary poisoning is not required.
----------------------	---

### 12.4. Mobility in soil

Biodegradation in soil:	Not applicable
-------------------------	----------------

### 12.5. Results of PBT and vPvB assessment

Regarding all available data on biotic and abiotic degradation, bioaccumulation and toxicity it can be stated that the substance does not fulfill the PBT criteria (not PBT) and not the vPvB criteria (not vPvB).

### 12.6. Other adverse effects

Not available.


## SECTION 13. DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

Waste disposal recommendations	Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal. Product is suitable for burning in an enclosed controlled burner for fuel value or disposal by supervised incineration at very high temperatures to prevent formation of undesirable combustion products. <b>Empty Container Warning:</b> Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. <b>DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.</b>
European List of Waste (LoW) code	Classified as hazardous waste according to European Union regulations Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

## SECTION 14. TRANSPORT INFORMATION

### 14.1. Land transport (ADR/ RID)

UN-No.	1077
Proper Shipping Name:	PROPYLENE
Hazard class:	2
Packing group:	Not applicable
Hazard label:	

Classification Code:	2F
Hazard identification number (HIN):	23
Tunnel restriction code (ADR):	2(B/D)
EAC code:	2YE
Environmental hazard:	No

### 14.2. Inland waterway transport (ADN)

UN-No.	1077
Proper Shipping Name:	PROPYLENE
Hazard class:	2
Packing group:	Not applicable

Hazard label:



Classification Code: 2F  
 Hazard identification number (HIN): 23  
 Environmental hazard: No

**14.3. Sea transport (IMDG)**

UN-No. 1077  
 Proper Shipping Name: PROPYLENE  
 Hazard class: 2.1  
 Packing group: Not applicable  
 Hazard label:



EmS-No. (Fire) F-D  
 EmS-No. (Spillage) S-U  
 Marine pollutant: No

**14.4. Air transport (IATA/ICAO)**

UN-No. 1077  
 Proper Shipping Name: PROPYLENE  
 Hazard class: 2.1  
 Packing group: Not applicable  
 Hazard label:



ERG Code: 10L  
 Environmental hazard: No

**14.5. Special precautions for user**

Always transport in closed containers. Ensure that persons transporting the product know what to do in the event of an accident or spillage. For information regarding Exposure Controls/Personal Protection see Section 8 of the SDS

**14.6. Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable

**SECTION 15. REGULATORY INFORMATION**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**15.1.1. EU-Regulations**

**Authorisations and/or restrictions on use (Annex XVII):**

Entry 40	Conditions of restriction
Substances classified as flammable gases category 1 or 2, flammable liquids	1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following: – metallic glitter intended mainly for decoration,

<p>categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.</p>	<ul style="list-style-type: none"> <li>- artificial snow and frost,</li> <li>- ‘whoopee’ cushions,</li> <li>- silly string aerosols,</li> <li>- imitation excrement,</li> <li>- horns for parties,</li> <li>- decorative flakes and foams,</li> <li>- artificial cobwebs,</li> <li>- stink bombs.</li> </ul> <p>2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with: ‘For professional users only’.</p> <p>3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/324/EEC.</p> <p>4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.</p>
---	---

Propene (CAS115-07-1) is not on the REACH Candidate List.

Propene (CAS115-07-1) is not on the REACH Annex XIV List.

Other information, restriction and prohibition regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer. Annex II - Not listed.

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances- (SEVESO III):  
 P2 Flammable gases.  
 Lower-tier requirements qualifying quantity: 50 tonnes:  
 Upper-tier requirements qualifying quantity: 200 tonnes.

Directive 2013/39/EU priority substances in the field of water policy (amending Directive 2006/60/EC – Water Framework Directive and Directive 2008/105/EC on environmental quality standards in the field of water policy): Not listed.

Regulation (EC) No 850/2004 on persistent organic pollutants: Annex III – Not listed.

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals: Not listed.

**15.1.2. Globally Harmonized System of Classification and Labelling of Chemicals (UN-GHS)**

**Labelling according to UN-GHS:**

Hazard pictogram(s)



GHS02: flame



GHS04: gas cylinder

Signal word(s)

Danger

Hazard Statement(s):

H220: Extremely flammable gas

H280: Contains gas under pressure; may explode if heated

Precautionary statement(s)

P210: Keep away from heat/sparks/open flames/... /hot surfaces.... No smoking. (Prevention)

P243: Take precautionary measures against static discharge

P377: Leaking gas fire: Do not extinguish, unless leak can be stopped safely. (Response)

P381: Eliminate all ignition sources if safe to do so. (Response)

### 15.1.3. National regulations

Germany	AwSV – water hazard Class ( WGK) nwg Storage class ( LGK) LGK 2A - Gases
Norway	Product Regulations – Chapter 2. Restrictions. Volatile organic compounds (VOC) in paint and varnish products.
Switzerland	Packaging Inks Regulation Annex 10 Listed ( Part A evaluated substances. List 1 . Specific migration limit 60 mg/kg)

### 15.2. Chemical safety assessment

Chemical Safety Report has been performed for propene.

## SECTION 16. OTHER INFORMATION

### 16.1. Indication of changes

Version	Date of change	Section	Description of changes
Version: 1.0	16/03/2010	All	Initial SDS. Version created according to Regulations (EC) No 1907/2006 (Article 31.1).
Version: 2.1	08/02/2011	All	Version created according to Regulation (EC) No 1272/2008 (Regulation CLP) & 453/2010.
Version: 2.2	08/08/2011	Heading; 1.3	Supplier name SIBUR-NEFTEKHIM JSC was renamed into SIBUR-KSTOVO LLC.
Version: 2.3	10/12/2012	All	1. Index No (CLP) for hazard impurities was added to Section 3. 2. Section 1; 2; 3; 4; 5; 6; 7; 10; 14 was fully reconfigured. 3. Section 8; 9; 11; 12 was fully updated. 4. The link to Appendix 2 was added to Section 7, 8. 5. Section 15; 16 were fully updated. 6. Appendix 2 to the eSDS was added.
Version 3.0	25/01/2019	All	All Sections were fully updated.

### 16.2. Abbreviations and acronyms

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
AGS	The German Committee on Hazardous Substances (Ausschuss für Gefahrstoffe – AGS)
BCF	Bioconcentration factor
DFG	Germany Research Foundation
DNEL	Derived No Effect Level
IMDG	International Maritime Dangerous Goods
ICAO-TI	Technical Instructions for the Safe Transport of Dangerous Goods by Air
K <sub>oc</sub>	Adsorption coefficient
K <sub>ow</sub>	octanol-water partition coefficient
LC50	Lethal Concentration to 50 % of a test population
LD50	Lethal Dose to 50% of a test population (Median Lethal Dose)
LOAEC	Lowest Observable Adverse Effect Concentration

LTEL	Long Term Exposure Limit
NIOSH	National Institute for Occupational Safety and Health ( <i>USA CDC</i> )
NOEC	No Observed Effect Concentration
NOAEL	No Observed Adverse Effect Level
OECD	Organization for Economic Co-operation and Development
OSHA	Occupational Safety & Health Administration ( <i>USA</i> )
PNEC	Predicted No Effect Concentration
PBT	Persistent, bioaccumulative, toxic chemical
vPvB	Very Persistent, Very Bioaccumulative
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SCOEL	Scientific Committee on Occupational Exposure Limits
STEL	Short Term Exposure Limit
STP	sewage treatment plant
STOT	Specific Target Organ Toxicity
(STOT) RE	Repeated Exposure
(STOT) SE	Single Exposure
TWA	Time Weighted Average
UN	United Nations
WGK	Wassergefährdungsklasse ( <i>German: Water Hazard Class</i> )

**16.3. Full text of H- and EUH-statements:**

H220	Flam. Gas 1	Extremely flammable gas
H280:	Liquefied gas	Contains gas under pressure; may explode if heated

**16.4. List of ES (exposure scenario) given in Appendix I to the extended SDS**

Propene is not classified for human health or the environment, is not a CMR and is not PBT or vPvB. An exposure assessment and the calculation of risk characterisation ratios are therefore not required. Relevant identified uses of the substance are described in the Annex to the SDS.

**16.5. Key literature references and sources**

**DOCUMENTS, PROVIDED BY LOA CONSORTIUM:**

CHEMICAL SAFETY REPORT to Propene.

**EU DIRECTIVES**

REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

Regulation (EC) No 1272/2008 REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Regulations. Commission regulation (EU) no 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH).

COMMISSION DECISION of 16 January 2001 amending Decision 2000/532/EC as regards the list of wastes (notified under document number (2001/118/EC).

**UK REGULATORY REFERENCES**



**PROPENE**

VERSION: 3.0

DATE CREATED: 25/01/2019

LANGUAGE: ENGLISH



Chemicals (Hazard Information & Packaging) Regulations. The Control of Substances Hazardous to Health Regulations 1988. Health and Safety at Work Act 1974.

**ENVIRONMENTAL LISTING**

Control of Pollution Act 1974.

**STATUTORY INSTRUMENTS**

Notification of New Substances Regulations (NONS) 1993. The Export and Import of Dangerous Chemicals Regulations 2005 number 928.

**GUIDANCE NOTES**

Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

**Training advice**

Personnel handling the product has to be acquainted demonstrably with its hazardous properties, with health and environmental protection principles related to the product and first aid principles.

**DISCLAIMER**

*This information is based on our current level of knowledge. This information may be subject to revision as new knowledge and experience becomes available, and SIBUR makes no warranties and assumes no liability in connection with any use of this information. Since SIBUR cannot be aware of all aspects of your business and the impact the REACH Regulation has for your company, SIBUR strongly encourages you to get familiar with the REACH Regulation in order to comply with its requirements and timelines.*

<b>ANNEX. RELEVANT IDENTIFIED USES OF THE SUBSTANCE</b>	
<b>Uses by workers in industrial settings</b>	
<b>Identifiers</b>	<b>Use descriptors</b>
<b>Formulation &amp; (re)packing of substances and mixtures</b>	<p><b>Process category (PROC):</b>            PROC 1: Use in closed process, no likelihood of exposure            PROC 2: Use in closed, continuous process with occasional controlled exposure            PROC 3: Use in closed batch process (synthesis or formulation)            PROC 4: Use in batch and other process (synthesis) where opportunity for exposure arises            PROC 5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)            PROC 8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities            PROC 8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities            PROC 9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)            PROC 14: Production of preparations or articles by tableting, compression, extrusion, palletisation            PROC 15: Use as laboratory reagent</p> <p><b>Environmental release category (ERC):</b>            ERC 2: Formulation of preparations</p>
<b>Distribution of substance</b>	<p><b>Process category (PROC):</b>            PROC 1: Use in closed process, no likelihood of exposure            PROC 2: Use in closed, continuous process with occasional controlled exposure            PROC 3: Use in closed batch process (synthesis or formulation)            PROC 4: Use in batch and other process (synthesis) where opportunity for exposure arises            PROC 8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities            PROC 8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities            PROC 9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)            PROC 15: Use as laboratory reagent</p> <p><b>Environmental release category (ERC):</b>            ERC 7: Industrial use of substances in closed systems</p>
<b>Use as a fuel</b>	<p><b>Process category (PROC):</b>            PROC 1: Use in closed process, no likelihood of exposure            PROC 2: Use in closed, continuous process with occasional controlled exposure            PROC 3: Use in closed batch process (synthesis or formulation)            PROC 4: Use in batch and other process (synthesis) where opportunity for</p>

	<p>exposure arises          PROC 8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities          PROC 8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities          PROC 16: Using material as fuel sources, limited exposure to unburned product to be expected</p> <p><b>Environmental release category (ERC):</b>          ERC 7: Industrial use of substances in closed systems</p>
<p><b>Use as an intermediate</b></p>	<p><b>Process category (PROC):</b>          PROC 1: Use in closed process, no likelihood of exposure          PROC 2: Use in closed, continuous process with occasional controlled exposure          PROC 3: Use in closed batch process (synthesis or formulation)          PROC 4: Use in batch and other process (synthesis) where opportunity for exposure arises          PROC 8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities          PROC 8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities          PROC 15: Use as laboratory reagent</p> <p><b>Environmental release category (ERC):</b>          ERC 6a: Industrial use resulting in manufacture of another substance (use of intermediates)</p> <p><b>Sector of end use:</b>          SU 8: Manufacture of bulk, large scale chemicals (including petroleum products)          SU 9: Manufacture of fine chemicals</p>
<p><b>Polymer Production</b></p>	<p><b>Process category (PROC):</b>          PROC 1: Use in closed process, no likelihood of exposure          PROC 2: Use in closed, continuous process with occasional controlled exposure          PROC 3: Use in closed batch process (synthesis or formulation)          PROC 4: Use in batch and other process (synthesis) where opportunity for exposure arises          PROC 5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)          PROC 6: Calendring operations          PROC 8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities          PROC 14: Production of preparations or articles by tableting, compression, extrusion, palletisation</p>

	<p><b>Environmental release category (ERC):</b>          ERC 6a: Industrial use resulting in manufacture of another substance (use of intermediates)</p> <p><b>Sector of end use:</b>          SU 10: Formulation [mixing] of preparations and/or re-packaging (excluding alloys)</p>
<b>Uses by professional workers</b>	
<b>Use as a fuel</b>	<p><b>Process category (PROC):</b>          PROC 1: Use in closed process, no likelihood of exposure          PROC 2: Use in closed, continuous process with occasional controlled exposure          PROC 3: Use in closed batch process (synthesis or formulation)          PROC 8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities          PROC 8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities          PROC 16: Using material as fuel sources, limited exposure to unburned product to be expected</p> <p><b>Environmental release category (ERC):</b>          ERC 9a: Wide dispersive indoor use of substances in closed systems          ERC 9b: Wide dispersive outdoor use of substances in closed systems</p>
<b>Use as a propellant</b>	<p><b>Process category (PROC):</b>          PROC 3: Use in closed batch process (synthesis or formulation)          PROC 5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)          PROC 9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)          PROC 11: Non industrial spraying          PROC 14: Production of preparations or articles by tableting, compression, extrusion, pelletisation</p> <p><b>Environmental release category (ERC):</b>          ERC 8a: Wide dispersive indoor use of processing aids in open systems          ERC 8d: Wide dispersive outdoor use of processing aids in open systems</p>
<b>Uses by consumers</b>	
<b>Use as a Fuel</b>	<p><b>Product Category used:</b>          PC 13: Fuels</p> <p><b>Environmental release category (ERC):</b>          ERC 9a: Wide dispersive indoor use of substances in closed systems          ERC 9b: Wide dispersive outdoor use of substances in closed systems</p> <p><b>Subsequent service life relevant for that use?:</b> No</p>

**END OF SAFETY DATA SHEET**